



\*F  
show non-standard options or features

# 22K TANDEM DUAL GOOSENECK

## STANDARD FEATURES

### Construction

- 12" @ 19 lb. I-Beam Main Frame & Tongue
- Stacked 3" Crosspieces on 16" Centers
- 6" Channel Side Rail with Knee Braces
- Bridged Frame, Torque Tube included 35'+

### Electrical

- Lifetime LED Lights, Rubber Mounted
- Mid-Span Amber Turn Signals
- USA Made Sealed Wiring Harness
- 7-Way RV-Style Plug

### Undercarriage

- 2 x 10,000 lb. Heavy Wall Oil Bath Axles
- 12 1/4" x 3 3/8" Brakes on All Hubs
- Slipper Spring Suspension, 42.5" Spread
- Electric Brakes with Breakaway Kit
- 8 x 235/80 R16 Tires, 16" Wheels

### Dimensions

- 22,500 GVWR, 16,000 lb. True Capacity
- 25' Flat Deck + 5' Cleated Beavertail
- 60" x 24" Stand-Up, Spring Assisted Ramps
- 34" Unloaded Deck Height
- 12" I-Beam Neck, 8' Tall, 54" Uprights

### Additional Features

- Nominal 2" Pressure Treated #1 Pine Deck
- Dual 15K Spring Loaded Jacks
- 25,000 lb. Adjustable Gooseneck Coupler
- Stake Pockets & Rub Rails with Spools
- HD Anti-Sail Mudflaps

### Finish

- High Pressure Phosphate Wash
- Primed Top & Bottom w/ Automotive Primer
- Two Top Coats of 2-Part PPG Black Gloss
- DOT Reflective Tape, Kraftsman Decals
- Safety & Operational Decals

Model	Size	Est. Tare
GS-22	102" x 25' + 5'	7,450 lb.
GS-22	102" x 30' + 5'	8,555 lb.
GS-22	102" x 35' + 5'	9,320 lb.

Standard features and parts sourcing are subject to change with no notice and no price change to the trailer, including after build agreement. All components used in construction of the trailer are guaranteed to support listed ratings.