



*Photo is meant to represent actual trailer and may show non-standard options or features

40K EXTREME DUTY HYDRAULIC DOVETAIL GOOSENECK

STANDARD FEATURES

Construction

- 14" @ 22 lb. I-Beam Main Frame & Tongue
- Pierced 3" Crosspieces on 16" Centers
- 8" Channel Side Rail with Knee Braces
- Bridged Frame, Torque Tube Included

Undercarriage

- 2 x 15,000 lb. Heavy Wall Oil Bath Axles
- 12 1/4" x 5" Brakes on All Hubs
- Slipper Spring Suspension, 49" Spread
- Electric Brakes with Breakaway Kit
- 8 x 215/75 R17.5 16 Ply Tires, 17.5" Wheels

Additional Features

- #1 Pressure Treated Pine
- Dual 50K 2-Speed Jacks
- 40,000 lb. Gooseneck Coupler, 3" Ball
- Stake Pockets & Rub Rails with Spools
- HD Anti-Sail Mudflaps

Electrical

- Lifetime LED Lights, Rubber Mounted
- Mid-Span Amber Turn Signals
- USA Made Sealed Wiring Harness
- 7-Way Semi-Style Plug

Dimensions

- 40,000 GVWR
- 18' Flat Deck + 12' Hydraulic Beavertail
- Hydraulic Tail Locks in the Travel Position
- 35" Unloaded Deck Height
- 14" I-Beam Neck, 8' Long, 56" Uprights

Finish

- High Pressure Phosphate Wash
- Primed Top & Bottom w/ Automotive Primer
- Two Top Coats of 2-Part PPG Black Gloss
- DOT Reflective Tape, Kraftsman Decals
- Safety & Operational Decals

Model	Size	Est. Tare
GX-40	102" x 18' + 12'	9,500 lb.
GX-40	102" x 23' + 12'	11,000 lb.
GX-40	102" x 28' + 12'	12,500 lb.

Standard features and parts sourcing are subject to change with no notice and no price change to the trailer, including after build agreement. All components used in construction of the trailer are guaranteed to support listed ratings.