



6' WIDE LOW SIDE SINGLE AXLE UTILITY

STANDARD FEATURES

* Photo represents actual trailer, may show options not included. See below for full specs.

Construction

- 2" x 2" Angle Top Rail and Uprights
- 3" x 2" A Main Frame, 12" Open Top Rail
- 2" x 2" Angle Gate Frame, Angle Uprights
- Fully Enclosed 4" x 2" Tubular Tailboard

Undercarriage

- 1 x 3,500 lb. EZ-Lube Axle, .180 Wall
- Idler Axle, Brakes Optional
- 4 Leaf Double Eye Suspensions
- 5 on 4.5" Bolt Pattern, 15" x 5" Wheels
- 2 x 205/75 R15 6 Ply Radial Tires

Additional Features

- Nominal 2" Pressure Treated #1 Pine Deck
- 2,000 lb. Bolt-On Tongue Jack
- Fixed 2" Coupler with Safety Chains
- Steps Front & Rear of each Fender
- 9" x 33" Smooth Steel Fenders

Electrical

- Rubber Mounted, DOT Approved Lights
- Marker Light on Formed Steps and Corners
- Factory Built Wiring Harness
- 4 Way Electrical Plug

Dimensions

- 2,990 GVWR
- 10' and 12' Single Axles Available
- 48" Mesh Tailgate, Fixed, w/ Spring Assist
- 18" Approx. Deck Height
- 3' Tongue, 3" x 2" Angle Construction

Finish

- High Pressure Phosphate Wash
- Primed Top & Bottom w/ Automotive Primer
- Two Top Coats of 2-Part PPG Black Gloss
- DOT Reflective Tape, Kraftsman Decals
- Safety & Operational Decals

Model	Size	Est. Tare
LS-6	76" x 10'	1,100 lb.
LS-6	76" x 12'	1,150 lb.

Standard features and parts sourcing are subject to change with no notice and no price change to the trailer, including after build agreement. All components used in construction of the trailer are guaranteed to support listed ratings.